



**Safety Data Sheet**  
**WL Plastics Polyethylene Pipe**  
**All Grades – All Colors – All Materials**  
SDS #: WL131

**Section 1 – Product and Company identification**

|   |  |  |  |
|---|--|--|--|
| <b>Product Name</b>                       | WL Plastics Polyethylene Pipe  |  |  |
| <b>SDS #</b>                              | WL131  |  |  |
| <b>Product Description</b>                | Polyethylene Pipe (various colors, and with and without external color stripes, and with and without internal color layer) |  |  |
| <b>Product Use</b>                        | Component for conveying gases, liquids and other fluid media   |  |  |
| <b>Company Identification</b>             | WL Plastics Corporation<br>3575 Lone Star Cir, Ste 300<br>Fort Worth, TX 76177   | Product Information:<br>Technical Information:<br>General Information: | 1-435-867-8908<br>1-435-867-8908<br>www.wlplastics.com |
| <b>24-Hour Emergency Telephone Number</b> | CHEMTREC – 1-800-424-9300  |  |  |

**Section 2 – Composition / Information on Ingredients**

| INGREDIENT NAME                               | CAS NUMBER | AMOUNT           |
|---|------------|------------------|
| Polyethylene                                  | 9002-88-4  | > 96% by weight  |
| Polyethylene Hexene Copolymer                 | 25213-02-9 | > 96% by weight  |
| Polyethylene Butene Copolymer                 | 25807-34-7 | > 96% by weight  |
| May include carbon black                      | 1333-86-4  | 0 - 4% by weight |
| May include flux calcined diatomaceous earth  | 68855-54-9 | <1% by weight    |
| May include crystalline silica (cristobalite) | 14464-46-1 | <1% by weight    |

**Section 3 – Hazards Identification**

|                           |  |
|---------------------------|--|
| <b>Emergency Overview</b> | Physical Appearance: <ul style="list-style-type: none"><li>○ Black polyethylene pipe</li><li>○ Black polyethylene pipe with external longitudinal contrasting color stripes</li><li>○ Black polyethylene pipe with contrasting internal color layer</li><li>○ Polyethylene pipe is supplied in straight lengths or coils</li></ul>   |
| <b>Hazards of Product</b> | <ul style="list-style-type: none"><li>○ This product is not a “Hazardous Chemical” as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.</li><li>○ Injury or death can result from product falling from a height or unexpected movement during storage, unloading or handling. Call 1-435-867-8908 for unloading and handling instructions or obtain unloading and handling instructions from <a href="http://www.wlplastics.com">www.wlplastics.com</a>.</li><li>○ Product surface can be slippery especially if there is water, snow or ice on the surface. Do not walk on product.</li><li>○ May contain an ingredient that can cause cancer. See Section 11. Not expected to be harmful if all recommendations in this SDS are followed. See Section 7 and Section 8.</li><li>○ EYE: Not expected to cause prolonged or significant eye irritation. If this material is heated, thermal burns may result from eye contact.</li><li>○ SKIN: Contact with the skin is not expected to cause prolonged or significant irritation or cause an allergic skin response. If this material is heated, thermal burns may result from skin contact.</li><li>○ INHALATION: Not expected to be harmful if inhaled. If this material is heated, fumes may be unpleasant and produce nausea and irritation of the upper respiratory tract.</li><li>○ INGESTION: Not expected to be harmful if swallowed.</li></ul> |

### Section 4 – First Aid Measures

- Eye contact:** Hot material: Flush eyes with plenty of cold water for at least 15 minutes. Do not remove contact lenses if worn. Seek medical assistance for mechanical removal of this material from the eye. The use of flush fluid, other than water, is not recommended.  
Cold material: Flush eyes with plenty of cold water. Get medical attention if irritation occurs.
- Skin contact:** Hot material: If burned by contact with hot material, flush skin immediately with large amounts of cold water. If possible, submerge area in cold water. No attempt should be made to detach polymer adhering to the skin or to remove clothing attached with molten material. Thermal burns require immediate medical attention.  
Cold material: Wash with soap and water.
- Inhalation:** If affected by fumes from heated material, remove from source of exposure and move the affected person into fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

### Section 5 – Fire Fighting Measures

- Flammability of the Product:** May be combustible at high temperatures.
- |             |           |                 |                |
|-------------|-----------|-----------------|----------------|
| <b>NFPA</b> | Health: 0 | Flammability: 1 | Instability: 0 |
| <b>HMIS</b> | Health: 0 | Flammability: 1 | Instability: 0 |
- Auto-ignition temperature:** Greater than 343°C (649°F)
- Flash point:** Above 300°C (572°F) decomposition occurs and flash of fumes may occur.
- Products of combustion:** Products of combustion are carbon oxides (CO, CO<sub>2</sub>). May also contain low levels of aldehydes, ketones, organic acids or hydrocarbons.
- Unusual fire/explosion hazards:** High dust concentrations have a potential for combustion or explosion. This material is not explosive as defined by established regulatory criteria.
- Fire-fighting media and instructions:** In case of fire, use water spray (fog), foam or dry chemicals. Do not use water jet.
- Protective clothing (fire):** Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

### Section 6 – Accidental Release Measures

- Protective measures:** Eliminate sources of ignition in vicinity of spilled material.
- Spill management:** If heated material is spilled, allow it to cool before proceeding with disposal methods. Shavings, chips or segments from cutting and cooled, spilled heated material may cause a slipping hazard. Isolate and contain to prevent entry into sewers and waterways. Sweep or vacuum shavings, chips, segments and cooled heated material and place in appropriate containers for disposal. Recycle where possible. Use appropriate safety equipment.
- Reporting:** USA regulations may require reporting spills of this material that could reach any surface waters. Report spills to local authorities and/or the National Response Center at (800) 424-8802 as appropriate or required.

### Section 7 – Handling and Storage

Read and observe all precautions published in *WL101 Joining And Field Procedures For Pipe* and *WL111 Unloading Guidelines For WL Plastics Polyethylene Pipe*. Call 1-435-867-8908 to obtain copies of WL101 and WL111 or obtain copies from [www.wlplastics.com](http://www.wlplastics.com).



**Safety Data Sheet**  
**WL Plastics Polyethylene Pipe**  
**All Grades – All Colors – All Materials**  
SDS #: WL131

**Section 7 – Handling and Storage (continued)**

**Precautionary measures:** Avoid heated material contact with eyes, skin and clothing. Avoid breathing vapor or fumes from heated material.

**Unusual handling hazards:** Potentially toxic / irritating fumes may evolve from heated material. At high temperatures, above 177°C (350°F), polyethylene can release vapors and gases that are irritating to mucous membranes of the eyes, mouth, throat and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, NTP, IARC (2A) and OSHA have listed formaldehyde as a probable human carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions.

**Section 8 – Exposure Controls and Personal Protection**

| Exposure limits:             | Component  | Exposure Limits   | Form   |
|------------------------------|--|---|--|
|                              | Particulates (Insoluble) Not Otherwise Specified (PNOS)  | 10 mg/m <sup>3</sup> TWA8 ACGIH   | Inhalable fraction Particulate matter containing no asbestos and crystalline silica <1%  |
|                              |  | 3 mg/m <sup>3</sup> TWA8 ACGIH  | Respirable fraction Particulate matter containing no asbestos and crystalline silica <1% |
|                              |  | 5 mg/m <sup>3</sup> TWA8 OSHA   | Respirable fraction  |
|                              |  | 15 mg/m <sup>3</sup> TWA8 OSHA  | Total dust   |
| <b>Personal protection:</b>  | Respiratory Protection:  | Use NIOSH-Approved respirator if unable to control airborne dust, fumes and vapor.                                    |  |
|                              | Ventilation:   | Local exhaust ventilation is recommended for control of airborne dust, fumes and vapor, especially in confined areas. |  |
|                              | Other Protective Equipment:  | Wear gloves and suitable eye protection.  |  |
| <b>Engineering controls:</b> | If dust is generated, provide local exhaust ventilation to keep exposure to airborne contaminants below exposure limits. |   |  |

**Section 9 – Physical and Chemical Properties**

|                                       |  |
|---------------------------------------|--|
| <b>Physical state and appearance:</b> | Polyethylene pipe is supplied in straight lengths or coils as black polyethylene pipe, or black polyethylene pipe with external longitudinal contrasting color stripes, or black polyethylene pipe with contrasting internal color layer, or yellow polyethylene pipe, or yellow polyethylene pipe with external longitudinal contrasting color stripes. |
| <b>Odor:</b>                          | Negligible   |
| <b>pH:</b>                            | NA   |
| <b>Vapor pressure:</b>                | NA   |
| <b>Vapor density (air = 1)</b>        | NA   |
| <b>Boiling point:</b>                 | NA   |
| <b>Solubility (in water):</b>         | Insoluble in water   |
| <b>Melting point:</b>                 | 100 - 135°C (212 - 275°F)  |
| <b>Specific gravity:</b>              | 0.93 – 0.99  |
| <b>Density:</b>                       | 0.93 – 0.99 g/cm <sup>3</sup>  |

## Section 10 – Stability and Reactivity

|  |   |
|--|---|
| <b>Chemical stability:</b>                   | This material is considered stable under ambient temperature and pressure and normally anticipated storage and handling conditions. |
| <b>Conditions to avoid:</b>                  | Avoid heating above recommended processing temperature.   |
| <b>Incompatibility with other materials:</b> | None  |
| <b>Hazardous decomposition products:</b>     | Carbon oxides   |
| <b>Hazardous polymerization:</b>             | Hazardous polymerization will not occur   |

## Section 11 – Toxicological Information

### Immediate Health Effects:

|  |   |
|--|---|
| <b>Acute oral toxicity:</b>                  | LD50 / Not known  |
| <b>Acute dermal toxicity:</b>                | LD50 / Not known  |
| <b>Acute inhalation toxicity:</b>            | LD50 / Not known  |
| <b>Eye irritation:</b>                       | Not expected to be irritating to the eyes.  |
| <b>Skin irritation:</b>                      | Not expected to be irritating to the skin.  |
| <b>Sensitization:</b>                        | Dermal – not a sensitizer / human   |
| <b>Additional toxicological information:</b> | <ul style="list-style-type: none"><li>○ This product contains POLYMERIZED OLEFINS. During thermal processing (&gt;177°C; &gt;350°F) polyethylene can release vapors and gases (aldehydes, ketones and organic acids) that are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a probable human carcinogen by NTP, IARC (2A) and OSHA based on animal data and limited epidemiological evidence.</li><li>○ Pigments containing carbon black, lead chromate, nickel, antimony or titanium compounds may have been incorporated into this product. The International Agency for Research on Cancer (IARC) has classified carbon black as a Group B carcinogen (possibly carcinogenic to humans) based on sufficient evidence in animals and inadequate evidence in humans. However, the pigments in this product are bound in a polymer matrix that severely limits its extractability, bioavailability and toxicity. The lead chromate pigment is also silica-encapsulated as well as bound in a polymer matrix. None of these pigments is likely to cause adverse health effects under recommended conditions of use.</li><li>○ Product marked “NSF-61” is safe for use with potable water (drinking water for human consumption).</li></ul> |

## Section 12 – Ecological Information

|                                       |   |
|---------------------------------------|---|
| <b>Ecotoxicity:</b>                   | This material is not expected to be harmful to aquatic organisms.   |
| <b>Environmental fate:</b>            | This material is not expected to be readily biodegradable.  |
| <b>Mobility:</b>                      | This product has not been found to migrate through soils.   |
| <b>Persistence and degradability:</b> | This product does not readily degrade. Under normal oxidation conditions, >99% of polyethylene will remain intact after exposure to microbial actions. Product will slowly change (embrittle) in the presence of sunlight, but will not fully break down. Product buried in landfill has been found to be stable over time. No toxic degradation products are known to be produced. |
| <b>Other ecological information:</b>  | Wildlife may ingest waste cuttings, shavings, segments or chips. Although not toxic, such materials may physically block the digestive system, causing starvation or death.   |

**Section 13 – Disposal Considerations**

**Disposal consideration / Waste information:** Recycle to process if possible. Waste cuttings, segments, chips and shavings should be swept up or vacuumed and placed in appropriate containers for disposal and to avoid runoff into waterways. This product as manufactured is a non-hazardous waste but may become contaminated upon use. If this material must be discarded, depending upon use and application, it may meet the criteria as hazardous waste as defined by the US EPA under RCRA (40 CFR 261) or other State or Local regulations. Consult an environmental professional to determine if local, regional or national regulations would classify this material or contaminated material as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable National, State, Provincial and Local regulations.

**Section 14 – Transport Information**

**US DOT** Not regulated as hazardous material or dangerous goods for transportation.  
**ICAO /IATA** Not regulated as hazardous material or dangerous goods for transportation.  
**IMO / IMDG** Not regulated as hazardous material or dangerous goods for transportation.  
**RID / ADR** Not regulated as hazardous material or dangerous goods for transportation.  
**TDG** Not regulated as hazardous material or dangerous goods for transportation.  
**Other transportation information:** The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**Section 15 – Regulatory Information**

|                                 |                                   |    |
|---------------------------------|-----------------------------------|----|
| <b>SARA 311/312 Categories:</b> | Immediate (acute) health effects  | No |
|                                 | Delayed (chronic) health effects  | No |
|                                 | Fire hazard                       | No |
|                                 | Sudden release of pressure hazard | No |
|                                 | Reactivity hazard                 | No |

**Regulatory Status:**

| Country        | Inventory | Status  |
|----------------|-----------|---|
| Australia      | AICS      | All components are included or otherwise exempt from inclusion on this inventory. |
| Canada         | DSL       | All components are included or otherwise exempt from inclusion on this inventory. |
| Canada         | NDSL      |   |
| China          | IECS      | All components are included or otherwise exempt from inclusion on this inventory. |
| European Union | EINECS    | All components are included or otherwise exempt from inclusion on this inventory. |
| European Union | ELINCS    |   |
| European Union | NLP       |   |
| Japan          | ENCS      | All components are included or otherwise exempt from inclusion on this inventory. |
| Korea          | ECL       | All components are included or otherwise exempt from inclusion on this inventory. |
| Philippines    | PICCS     | All components are included or otherwise exempt from inclusion on this inventory. |
| United States  | TSCA      | All components are included or otherwise exempt from inclusion on this inventory. |

