



### OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI 14 - Plastics Piping System Components and Related Materials

This is the Official Listing recorded on January 25, 2022.

**WL Plastics Corporation**  
**3575 Lone Star Circle**  
**Suite 300**  
**Fort Worth, TX 76177**  
**682-831-2727**

**Facility: Cedar City, UT**

#### Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe <sup>+</sup> [G]	PE 4710	WL Plastics UT / WLP UT	ASTM D3035
1/2" - 24" DR 7			
1/2" - 36" DR 9			
1/2" - 36" DR 9.3			
1/2" - 36" DR 11			
1/2" - 42" DR 13			
1/2" - 48" DR 15.5			
1/2" - 54" DR 17			
1/2" - 54" DR 21			
1/2" - 54" DR 26			
1/2" - 54" DR 32.5			
Pipe <sup>+</sup> [1] [G]	PE 4710	WL Plastics UT / WLP UT	AWWA C901
3/4" - 3" SDR 7			
3/4" - 3" SDR 7.3			
3/4" - 3" SDR 9			
3/4" - 3" SDR 11			
Pipe <sup>+</sup> [G]	PE 3408/PE 4710	WL Plastics UT / WLP UT	AWWA C906
4" - 24" DR 7			
4" - 36" DR 7.3			
4" - 36" DR 9			
4" - 36" DR 9.3			
4" - 36" DR 11			
4" - 42" DR 13.5			
4" - 48" DR 15.5			
4" - 54" DR 17			
4" - 54" DR 21			
4" - 54" DR 26			
4" - 54" DR 32.5			
Pipe <sup>+</sup> [G]	PE 4710		

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



<i>WL Plastics UT /</i>	<i>ASTM F714</i>
<i>WLP UT</i>	
3" - 24" DR 7	
3" - 36" DR 7.3	
3" - 36" DR 8.3	
3" - 36" DR 9	
3" - 36" DR 9.3	
3" - 36" DR 11	
3" - 42" DR 13.5	
3" - 48" DR 15.5	
3" - 54" DR 17	
3" - 54" DR 21	
3" - 54" DR 26	
3" - 54" DR 32.5	
3" - 54" DR 41	

- \* These products also meet the requirements for PE 3408 per ASTM D3350-02a.
- + Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.
- [1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.
- [G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

**Facility: Elizabethtown, KY**

**Potable Water - Pipe and Fittings**

<b>Product Type</b>	<b>Material Type</b>	<b>Trade Name</b>	<b>Product Standard</b>
<i>Pipe</i> <sup>+</sup> [G]	<i>PE 4710</i>	<i>WL Plastics KY / WLP KY</i>	<i>ASTM D3035</i>
1/2" - 24" DR 7			
1/2" - 36" DR 9			
1/2" - 36" DR 9.3			
1/2" - 36" DR 11			
1/2" - 42" DR 13.5			
1/2" - 48" DR 15.5			
1/2" - 54" DR 17			
1/2" - 54" DR 21			
1/2" - 54" DR 26			
1/2" - 54" DR 32.5			
<i>Pipe</i> <sup>+</sup> [1] [G]	<i>PE 4710</i>	<i>WL Plastics KY / WLP KY</i>	<i>AWWA C901</i>
3/4" - 3" SDR 7			
3/4" - 3" SDR 7.3			
3/4" - 3" SDR 9			
3/4" - 3" SDR 11			
<i>Pipe</i> <sup>*</sup> + [G]	<i>PE 3408/PE 4710</i>	<i>WL Plastics KY / WLP KY</i>	<i>AWWA C906</i>

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



4" - 24" DR 7  
 4" - 24" DR 7.3  
 4" - 36" DR 9  
 4" - 36" DR 9.3  
 4" - 36" DR 11  
 4" - 42" DR 13.5  
 4" - 48" DR 15.5  
 4" - 54" DR 17  
 4" - 54" DR 21  
 4" - 54" DR 26  
 4" - 54" DR 32.5

Pipe<sup>+</sup> [G]

PE 4710

WL Plastics KY /  
WLP KY

ASTM F714

3" - 24" DR 7  
 3" - 24" DR 7.3  
 3" - 24" DR 8.3  
 3" - 36" DR 9  
 3" - 36" DR 9.3  
 3" - 36" DR 11  
 3" - 42" DR 13.5  
 3" - 48" DR 15.5  
 3" - 54" DR 17  
 3" - 54" DR 21  
 3" - 54" DR 26  
 3" - 54" DR 32.5  
 3" - 54" DR 41

\* These products also meet the requirements for PE 3408 per ASTM D3350-02a.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

[1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

Facility: Rapid City, SD

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe <sup>+</sup> [1] [G]	PE 4710	WL Plastics SD / WLP SD	AWWA C901
3/4" - 3" SDR 7			
3/4" - 3" SDR 7.3			
3/4" - 3" SDR 9			
3/4" - 3" SDR 11			
Pipe <sup>+</sup> [G]	PE 3408/PE 4710	WL Plastics SD / WLP SD	AWWA C906
4" - 24" DR 7			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



4" - 36" DR 7.3  
 4" - 36" DR 9  
 4" - 36" DR 9.3  
 4" - 36" DR 11  
 4" - 42" DR 13.5  
 4" - 48" DR 15.5  
 4" - 54" DR 17  
 4" - 54" DR 21  
 4" - 54" DR 13.5  
 4" - 54" DR 26  
 4" - 54" DR 32.5

Pipe<sup>+</sup> [G]

PE 4710

WL Plastics SD /  
WLP SD

ASTM D3035

1/2" - 24" DR 7  
 1/2" - 36" DR 9  
 1/2" - 36" DR 9.3  
 1/2" - 36" DR 11  
 1/2" - 42" DR 13.5  
 1/2" - 48" DR 15.5  
 1/2" - 54" DR 17  
 1/2" - 54" DR 21  
 1/2" - 54" DR 26  
 1/2" - 54" DR 32.5

Pipe<sup>+</sup> [G]

PE 4710

WL Plastics SD /  
WLP SD

ASTM F714

3" - 24" DR 7  
 3" - 36" DR 7.3  
 3" - 36" DR 8.3  
 3" - 36" DR 9  
 3" - 36" DR 9.3  
 3" - 36" DR 11  
 3" - 42" DR 13.5  
 3" - 48" DR 15.5  
 3" - 54" DR 17  
 3" - 54" DR 21  
 3" - 54" DR 26  
 3" - 54" DR 32.5  
 3" - 54" DR 41

\* These products also meet the requirements for PE 3408 per ASTM D3350-02a.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

[1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



Facility: Titusville, PA

Gas Applications - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe *	PE 2708	WL Plastics PA/WLP PA	ASTM D2513
1/2" CTS - .090 WALL			
3/4" CTS - .090 WALL			
1 1/8" CTS - .099 WALL, 0.090 WALL			
1/2" IPS SDR 9.3			
3/4" IPS SDR 11			
1" IPS SDR 11			
1 1/4" IPS SDR 10,11			
1 1/2" IPS SDR 11			
2" IPS SDR 11			
3" IPS SDR 11,11.5			
4" IPS SDR 11,11.5,13.5			
Pipe *	PE 4710	WL Plastics PA/WLP PA	ASTM D2513
1/2" CTS - .090 WALL, .062 WALL			
3/4" CTS - .090 WALL			
1" CTS -.121, .101, .101, .099, .090 WALL			
1 1/4" CTS - .090 WALL			
3/4" IPS SDR 7.3,9,11			
1" IPS SDR 7.3,9,11			
1 1/4" IPS SDR 7.3,9,11			
1 1/2" IPS SDR 7.3,9,11			
2" IPS SDR 7.3,9,11,13.5,15.5,17			
3" IPS SDR 7.3,9,11,13.5,15.5,17			
4" IPS SDR 7.3,9,11,13.5,15.5,17			
6" IPS SDR 9,11,13.5,15.5,17			
8" IPS SDR 11,13.5,15.5,17			
10" IPS SDR 13.5,15.5,17			
12" IPS SDR 15.5,17			
Pipe *	PE 2708	WL Plastics PA/WLP PA	CSA B137.4
1/2" CTS .090 wall			
1" CTS .099 wall			
1 1/4" SDR 10			
3/4" - 2" SDR 11			

\* Product is authorized to bear the cNSF Mark.

Potable Water - Pipe and Fittings

Product Type	Material Type	Trade Name	Product Standard
Pipe \$ * +	PE 3608/4710	WL Plastics PA/WLP PA	ASTM D2239
1/2" - 3" SIDR 11.5			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



3/4" - 2"	SIDR 5.3			
3/4" - 2"	SIDR 7			
3/4" - 2"	SIDR 9			
3/4" - 4"	SIDR 15			
1/2" - 3"	SIDR 19			
Pipe <sup>\$ * +</sup>		PE 3608/4710	WL Plastics PA/WLP PA	ASTM D3035
1/2" - 24"	DR 7			
1/2" - 24"	DR 9			
1/2" - 24"	DR 9.3			
1/2" - 24"	DR 11			
1/2" - 24"	DR 13.5			
1/2" - 24"	DR 15.5			
1/2" - 24"	DR 17			
1/2" - 24"	DR 21			
1/2" - 24"	DR 26			
1/2" - 24"	DR 32.5			
Tubing <sup>\$ * +</sup>		PE 3608/4710	WL Plastics PA/WLP PA	ASTM D2737
3/4" - 2"	SDR 9			
Pipe <sup>\$ * +</sup>		PE 3608/4710	WL Plastics PA/WLP PA	ASTM F714
3" - 24" IPS and DIPS	DR 7.3			
3" - 24" IPS and DIPS	DR 9			
3" - 24" IPS and DIPS	DR 9.3			
3" - 24" IPS and DIPS	DR 11			
3" - 24" IPS and DIPS	DR 13.5			
3" - 24" IPS and DIPS	DR 15.5			
3" - 24" IPS and DIPS	DR 17			
3" - 24" IPS and DIPS	DR 21			
3" - 24" IPS and DIPS	DR 26			
3" - 24" IPS and DIPS	DR 32.5			
Tubing <sup>* +</sup>		PE 4710	WL Plastics PA/WLP PA	AWWA C901
3/4" - 2" CTS	SDR 9			
Pipe <sup>\$ * +</sup>		PE 3608/4710	WL Plastics PA/WLP PA Blue	ASTM D2239
1/2" - 3"	SIDR 11.5			
3/4" - 2"	SIDR 5.3			
3/4" - 2"	SIDR 7			
3/4" - 2"	SIDR 9			
3/4" - 4"	SIDR 15			
1/2" - 3"	SIDR 19			
Pipe <sup>\$ * +</sup>		PE 3608/4710	WL Plastics PA/WLP PA Blue	ASTM D3035
1/2" - 24"	DR 7			
1/2" - 24"	DR 9			
1/2" - 24"	DR 9.3			
1/2" - 24"	DR 11			

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



1/2" - 24" DR 13.5  
 1/2" - 24" DR 15.5  
 1/2" - 24" DR 17  
 1/2" - 24" DR 21  
 1/2" - 24" DR 26  
 1/2" - 24" DR 36

Tubing<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA Blue ASTM D2737

3/4" - 2" SDR 9

Pipe<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA Blue ASTM F714

3" - 24" IPS and DIPS DR 7.3  
 3" - 24" IPS and DIPS DR 9  
 3" - 24" IPS and DIPS DR 9.3  
 3" - 24" IPS and DIPS DR 11  
 3" - 24" IPS and DIPS DR 13.5  
 3" - 24" IPS and DIPS DR 15.5  
 3" - 24" IPS and DIPS DR 17  
 3" - 24" IPS and DIPS DR 21  
 3" - 24" IPS and DIPS DR 26  
 3" - 24" IPS and DIPS DR 32.5

Tubing<sup>\* +</sup> PE 4710 WL Plastics PA/WLP PA Blue AWWA C901

3/4" - 2" CTS SDR 9

Pipe<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA BLUE ICE ASTM D2239

3/4" - 2" SIDR 7  
 3/4" - 2" SIDR 9  
 3/4" - 2" SIDR 15

Tubing<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA BLUE ICE ASTM D2737

3/4" - 2" SDR 9

Tubing<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA BLUESTRIPE ASTM D2737

3/4" - 2" SDR 9

Pipe<sup>\$ \* +</sup> PE 3608/4710 WL Plastics PA/WLP PA BLUESTRIPE ASTM D3035

1/2" - 24" DR 7  
 1/2" - 24" DR 9  
 1/2" - 24" DR 9.3  
 1/2" - 24" DR 11  
 1/2" - 24" DR 13.5  
 1/2" - 24" DR 15.5  
 1/2" - 24" DR 17  
 1/2" - 24" DR 21  
 1/2" - 24" DR 26  
 1/2" - 24" DR 32.5

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



Pipe <sup>\$ * +</sup>	PE 3608/4710	WL Plastics PA/WLP PA BLUESTRIPE	ASTM F714
3" - 24" IPS and DIPS	DR 7.3		
3" - 24" IPS and DIPS	DR 9		
3" - 24" IPS and DIPS	DR 9.3		
3" - 24" IPS and DIPS	DR 11		
3" - 24" IPS and DIPS	DR 13.5		
3" - 24" IPS and DIPS	DR 15.5		
3" - 24" IPS and DIPS	DR 17		
3" - 24" IPS and DIPS	DR 21		
3" - 24" IPS and DIPS	DR 26		
3" - 24" IPS and DIPS	DR 32.5		

Pipe <sup>\$ * +</sup>	PE 3608/4710	WL Plastics PA/WLP PA BLUESTRIPE	ASTM D2239
3/4" - 2" SIDR	5.3		
3/4" - 2" SIDR	7		
3/4" - 2" SIDR	9		
1/2" - 2" SIDR	11.5		
3/4" - 4" SIDR	15		
1" - 2" SIDR	19		

Tubing <sup>* +</sup>	PE 4710	WL Plastics PA/WLP PA BLUESTRIPE	AWWA C901
3/4" - 2" CTS	SDR 9		

Pipe <sup>\$ * +</sup>	PE 3608/4710	WL Plastics PA/WLP PA BLUESTRIPE	AWWA C906
4" - 12" SDR	7		
4" - 12" SDR	9		
4" - 12" SDR	11		
4" - 12" SDR	13.5		
4" - 12" SDR	15.5		
4" - 12" SDR	17		
4" - 12" SDR	21		
4" - 12" SDR	26		
4" - 12" SDR	32.5		

Pipe <sup>\$ * +</sup>	PE 3608/4710	WL Plastics PA/WLP PA	AWWA C906
4" - 12" SDR	7		
4" - 12" SDR	9		
4" - 12" SDR	11		
4" - 12" SDR	13.5		
4" - 12" SDR	15.5		
4" - 12" SDR	17		
4" - 12" SDR	21		
4" - 12" SDR	26		
4" - 12" SDR	32.5		

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.





\$ These products also meet the requirements for PE 3408 per ASTM D3350-02a.

\* Product tested and Certified for Cold 23°C (73°F) applications only.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.

9 of 9