



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 14 - Plastics Piping System Components and Related Materials

This is the Official Listing recorded on September 24, 2019.

WL Plastics Corporation
3575 Lone Star Circle
Suite 300
Fort Worth, TX 76177
682-831-2727

Facility: Cedar City, UT

Gas Applications - Pipe and Fittings

| Product Type | Material Type | Trade Name | Product Standard |
|----------------|---------------------------------|-------------|------------------|
| Pipe | PE 4710 | WL Plastics | ASTM D2513 |
| 1/2" IPS DR | 9.33,11 | | |
| 3/4" IPS Sch | 40DR 11 | | |
| 1" IPS DR | 9.33,9.9,11,13.5 | | |
| 1 1/4" IPS Sch | 40DR 6,9.33,10,11,13.5,17 | | |
| 1 1/2" IPS Sch | 40DR 11,13.5,17 | | |
| 2" IPS Sch | 40DR 9.33,11,13.5,17,21 | | |
| 2 1/2" IPS DR | 11,13.5,17,21 | | |
| 3" IPS Sch | 40DR 9.33,11,11.5,13.5,17,21 | | |
| 3 1/2" IPS DR | 11,13.5,17,21 | | |
| 4" IPS DR | 9.33,11,11.5,13.5,17,19,21 | | |
| 5" IPS DR | 11,13.5,17,21,21.6 | | |
| 6" IPS DR | 11,11.5,13.5,17,21,23.7,23,32.5 | | |
| 8" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 10" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 12" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 14" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 16" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 18" IPS DR | 11,11.5,13.5,17,21,26,32.5 | | |
| 20" IPS DR | 11,11.5,13.5,17,21,23,32.5 | | |
| 22" IPS DR | 11.5,13.5,17,21,23,32.5 | | |

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



24" IPS DR 13.5,17,21,26,32.5

Potable Water - Pipe and Fittings

| Product Type | | Material Type | Trade Name | Product Standard |
|---------------------------|---------|-----------------|----------------------------|------------------|
| Pipe ⁺ [G] | | PE 4710 | WL Plastics UT / WLP UT | ASTM D3035 |
| 1/2" - 24" | DR 7 | | | |
| 1/2" - 36" | DR 9 | | | |
| 1/2" - 36" | DR 9.3 | | | |
| 1/2" - 36" | DR 11 | | | |
| 1/2" - 42" | DR 13 | | | |
| 1/2" - 48" | DR 15.5 | | | |
| 1/2" - 54" | DR 17 | | | |
| 1/2" - 54" | DR 21 | | | |
| 1/2" - 54" | DR 26 | | | |
| 1/2" - 54" | DR 32.5 | | | |
| Pipe ⁺ [1] [G] | | PE 4710 | WL Plastics UT / WLP UT | AWWA C901 |
| 3/4" - 3" | SDR 7 | | | |
| 3/4" - 3" | SDR 7.3 | | | |
| 3/4" - 3" | SDR 9 | | | |
| 3/4" - 3" | SDR 11 | | | |
| Pipe [*] + [G] | | PE 3408/PE 4710 | WL Plastics UT / WLP UT | AWWA C906 |
| 4" - 24" | DR 7 | | | |
| 4" - 36" | DR 7.3 | | | |
| 4" - 36" | DR 9 | | | |
| 4" - 36" | DR 9.3 | | | |
| 4" - 36" | DR 11 | | | |
| 4" - 42" | DR 13.5 | | | |
| 4" - 48" | DR 15.5 | | | |
| 4" - 54" | DR 17 | | | |
| 4" - 54" | DR 21 | | | |
| 4" - 54" | DR 26 | | | |
| 4" - 54" | DR 32.5 | | | |
| Pipe ⁺ [G] | | PE 4710 | WL Plastics UT / WLP UT | ASTM F714 |
| 3" - 24" | DR 7 | | | |
| 3" - 36" | DR 7.3 | | | |
| 3" - 36" | DR 8.3 | | | |
| 3" - 36" | DR 9 | | | |
| 3" - 36" | DR 9.3 | | | |
| 3" - 36" | DR 11 | | | |
| 3" - 42" | DR 13.5 | | | |
| 3" - 48" | DR 15.5 | | | |
| 3" - 54" | DR 17 | | | |
| 3" - 54" | DR 21 | | | |
| 3" - 54" | DR 26 | | | |
| 3" - 54" | DR 32.5 | | | |

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



3" - 54"

DR 41

* These products also meet the requirements for PE 3408 per ASTM D3350-02a.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

[1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

Facility: Elizabethtown, KY

Potable Water - Pipe and Fittings

| Product Type | Material Type | Trade Name | Product Standard |
|---------------------------|-----------------|-------------------------|------------------|
| Pipe ⁺ [G] | PE 4710 | WL Plastics KY / WLP KY | ASTM D3035 |
| 1/2" - 24" | DR 7 | | |
| 1/2" - 36" | DR 9 | | |
| 1/2" - 36" | DR 9.3 | | |
| 1/2" - 36" | DR 11 | | |
| 1/2" - 42" | DR 13.5 | | |
| 1/2" - 48" | DR 15.5 | | |
| 1/2" - 54" | DR 17 | | |
| 1/2" - 54" | DR 21 | | |
| 1/2" - 54" | DR 26 | | |
| 1/2" - 54" | DR 32.5 | | |
| Pipe ⁺ [1] [G] | PE 4710 | WL Plastics KY / WLP KY | AWWA C901 |
| 3/4" - 3" | SDR 7 | | |
| 3/4" - 3" | SDR 7.3 | | |
| 3/4" - 3" | SDR 9 | | |
| 3/4" - 3" | SDR 11 | | |
| Pipe [*] + [G] | PE 3408/PE 4710 | WL Plastics KY / WLP KY | AWWA C906 |
| 4" - 24" | DR 7 | | |
| 4" - 24" | DR 7.3 | | |
| 4" - 36" | DR 9 | | |
| 4" - 36" | DR 9.3 | | |
| 4" - 36" | DR 11 | | |
| 4" - 42" | DR 13.5 | | |
| 4" - 48" | DR 15.5 | | |
| 4" - 54" | DR 17 | | |
| 4" - 54" | DR 21 | | |
| 4" - 54" | DR 26 | | |
| 4" - 54" | DR 32.5 | | |
| Pipe ⁺ [G] | PE 4710 | WL Plastics KY / WLP KY | ASTM F714 |
| 3" - 24" | DR 7 | | |
| 3" - 24" | DR 7.3 | | |

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



| | |
|----------|---------|
| 3" - 24" | DR 8.3 |
| 3" - 36" | DR 9 |
| 3" - 36" | DR 9.3 |
| 3" - 36" | DR 11 |
| 3" - 42" | DR 13.5 |
| 3" - 48" | DR 15.5 |
| 3" - 54" | DR 17 |
| 3" - 54" | DR 21 |
| 3" - 54" | DR 26 |
| 3" - 54" | DR 32.5 |
| 3" - 54" | DR 41 |

* These products also meet the requirements for PE 3408 per ASTM D3350-02a.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

[1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.

Facility: Rapid City, SD

Potable Water - Pipe and Fittings

| Product Type | Material Type | Trade Name | Product Standard |
|---------------------------|-----------------|-------------------------|------------------|
| Pipe ⁺ [1] [G] | PE 4710 | WL Plastics SD / WLP SD | AWWA C901 |
| 3/4" - 3" | SDR 7 | | |
| 3/4" - 3" | SDR 7.3 | | |
| 3/4" - 3" | SDR 9 | | |
| 3/4" - 3" | SDR 11 | | |
| Pipe ⁺ [G] | PE 3408/PE 4710 | WL Plastics SD / WLP SD | AWWA C906 |
| 4" - 24" | DR 7 | | |
| 4" - 36" | DR 7.3 | | |
| 4" - 36" | DR 9 | | |
| 4" - 36" | DR 9.3 | | |
| 4" - 36" | DR 11 | | |
| 4" - 42" | DR 13.5 | | |
| 4" - 48" | DR 15.5 | | |
| 4" - 54" | DR 17 | | |
| 4" - 54" | DR 21 | | |
| 4" - 54" | DR 13.5 | | |
| 4" - 54" | DR 26 | | |
| 4" - 54" | DR 32.5 | | |
| Pipe ⁺ [G] | PE 4710 | WL Plastics SD / WLP SD | ASTM D3035 |
| 1/2" - 24" | DR 7 | | |
| 1/2" - 36" | DR 9 | | |

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.



| | |
|------------|---------|
| 1/2" - 36" | DR 9.3 |
| 1/2" - 36" | DR 11 |
| 1/2" - 42" | DR 13.5 |
| 1/2" - 48" | DR 15.5 |
| 1/2" - 54" | DR 17 |
| 1/2" - 54" | DR 21 |
| 1/2" - 54" | DR 26 |
| 1/2" - 54" | DR 32.5 |

Pipe⁺ [G]

PE 4710

WL Plastics SD /
WLP SD

ASTM F714

| | |
|----------|---------|
| 3" - 24" | DR 7 |
| 3" - 36" | DR 7.3 |
| 3" - 36" | DR 8.3 |
| 3" - 36" | DR 9 |
| 3" - 36" | DR 9.3 |
| 3" - 36" | DR 11 |
| 3" - 42" | DR 13.5 |
| 3" - 48" | DR 15.5 |
| 3" - 54" | DR 17 |
| 3" - 54" | DR 21 |
| 3" - 54" | DR 26 |
| 3" - 54" | DR 32.5 |
| 3" - 54" | DR 41 |

* These products also meet the requirements for PE 3408 per ASTM D3350-02a.

+ Material complies with NSF/ANSI/CAN 61 health effects requirements when tested at 73° F.

[1] Special sizes may be acceptable for engineered applications, due to system conditions or special local requirements. It is the responsibility of the end user to ensure that the product is suitable for the intended application.

[G] Product is Certified to NSF/ANSI 372 and conforms with the lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

NOTE: Only products bearing the NSF Mark on the product, product packaging, and/or documentation shipped with the product are Certified.