

# WL108 SHIPPING DATA



## NOTICE

The information in this publication is for estimating purposes only. Truckload quantities herein were developed for a maximum load weight of 47,000 lbs (21,315 kg) and maximum level load dimensions of 102-in (2.59 m) high x 102-in (2.59 m) wide that provide a 13 ½ ft (4.11 m) overall height when loaded on a flatbed trailer having a 60-in (1.52 m) deck height. See table footnotes for additional information. Special load configurations may be available, and actual truckload quantities may differ from the information in this publication depending upon state, provincial, or federal regulatory requirements, and the size and capacity of commercial equipment available at the time of shipment. Contact WL Plastics Customer Service for specific order freight quote information. WL Plastics Corporation has made every reasonable effort to ensure accuracy, but the information in this publication may not be complete, especially for special or unusual applications. The user of the information in this publication assumes all risk associated with its use.

## WL Plastics Pipe Sizing and Weight Publications

WL102 IPS

WL104 DIPS

WL130 FM Approved

**Table 1 Standard Truckload Quantities – Coiled Pipe<sup>1</sup>**

Pipe Size	Coil Length, ft	Pipe DR	Number of Coils per Pallet or Set <sup>2</sup>	Number of Coils per Truckload	Footage per Truckload
1" IPS	500	7 – 11	7 per pallet	140	70,000
1 1/4" IPS	500	7 – 11	5 per pallet	100	50,000
1 1/2" IPS	500	7 – 11	8 per set	64	32,000
	2000	7 – 11	3 per set	24	48,000
2" IPS	500	7 – 17	7 per set	56	28,000
	500	7 – 17	7 per pallet	49	24,500
	2000	7 – 17	2 per set	16	32,000
3" IPS	500	7 – 17	2 or 4 per set	26	13,000
	1000	7 – 17	1 or 2 per set	13	13,000
4" IPS	500	7 – 17	1 or 3 per set	13	6,500
	800	7 – 17	2 per set	12	9,600
6" IPS	500	7 – 17	2 per set	8 <sup>3</sup>	4,000 <sup>3</sup>
6" IPS	500	7 – 17	2 per set	6 <sup>4</sup>	3,000 <sup>4</sup>

<sup>1</sup> WL Plastics standard coil size and packaging. Special coil sizing or packaging may be available. Contact WL Plastics Customer Service for information. Standard truckload capacity based for 48-ft (14.6 m) long flatbed trailer and DOT maximum load weight and maximum load dimensions 102" high x 102" wide (2.6 m high x 2.6 m wide). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.  
<sup>2</sup> Coils on pallets are laid flat (vertical coil centerline) on non-return wood pallets and strapped in layers to the pallet. Coils packaged in sets are oriented vertically (horizontal coil centerline) and strapped together in sets without pallets or additional dunnage.  
<sup>3</sup> 53-ft (16.5 m) step-deck trailer with 42-in (1.07 m) maximum deck height required.  
<sup>4</sup> 48-ft (14.6 m) step-deck trailer with 42-in (1.07 m) maximum deck height required.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA

**Table 2 Standard Coil Dimensions<sup>1,7</sup> – Coiled Pipe**

Pipe Size	Coil Length, ft	Pipe DR	Coil Outside Diameter <sup>2</sup> , in.	Coil Inside Diameter <sup>3</sup> , in.	Coil Width <sup>4</sup> , in.
1" IPS	500	7 – 11	47	30	11 ½
1 1/4" IPS	500	7 – 11	48	30	15 ½
1 1/2" IPS	500	7 – 11	74	50	10
	2000	7 – 11	76 ½	50	31 ½
2" IPS	500	7 – 17	79	50	13 <sup>5</sup>
	2000	7 – 17	79	50	44 ½ <sup>6</sup>
3" IPS	500	7 – 17	96	70	23 <sup>6</sup>
	1000	7 – 17	96	70	45 <sup>6</sup>
4" IPS	500	7 – 17	96	70	40 <sup>6,7</sup>
	800	7 – 17	102	70	46 <sup>6</sup>
6" IPS	500	7 – 17	120 <sup>8</sup>	70	48

<sup>1</sup> WL Plastics standard coil packaging. Special packaging and coil lengths may be available. Contact WL Plastics Customer Service for information.

<sup>2</sup> Outside diameter dimensions are approximate. The tail end of the coil is strapped to the coil body to the extent practical, but may extend beyond the coil outside diameter by up to 3 pipe diameters.

<sup>3</sup> Inside diameter dimensions are approximate, and may include a small taper from one side of the coil to the other.

<sup>4</sup> Coil width dimensions are approximate.

<sup>5</sup> 12 ¾" wide for DR17.

<sup>6</sup> 1" wider for DR17.

<sup>7</sup> Contact WL Plastics Customer Service for special coil sizing.

<sup>8</sup> Step-deck trailers required. See Table 1.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



## Table 3A Standard Truckload Quantities – IPS-DR Pipe Joints<sup>1</sup> Multi-Layer Pipe Bundles

Length IPS Pipe Size	40 ft Joint					50 ft Joint					
	Joints / Bundle	Pipe DR	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pipe DR	Bundles / Truckload	Joints / Truckload	Feet / Truckload	
2	50	5	18	900	36,000	50	5	14	700	35,000	
		6 – 6.3	20	1,000	44,000		6 – 6.3	18	900	45,000	
		7 – 17	24	1,200	48,000		7 – 7.3	20	1000	50,000	
							9 – 17	24	1200	60,000	
2 ½	44	5	14	616	24,640	44	5	12	528	26,400	
		6	16	704	28,160		6 – 6.3	14	616	30,800	
		6.3 – 7	18	792	31,680		7 – 7.3	16	704	35,200	
		7.3 – 17	20	880	35,200		9	18	792	39,600	
							11 – 17	20	880	44,000	
3	50	5	8	400	16,000	50	5	6	300	15,000	
		6 – 6.3	10	500	20,000		6 – 7	8	400	20,000	
		7 – 7.3	12	600	24,000		7.3 – 9	10	500	25,000	
		9 – 21	14	700	28,000		11 – 17	14	700	35,000	
4	57	7 – 7.3 <sup>2</sup>	6	342	13,680	57	9 – 11 <sup>2</sup>	6	342	17,100	
		9 – 32.5	8	456	18,240		13.5 – 32.5	8	456	22,800	
	29	5	5	8	232	9,280	29	5	6	174	8,700
			6 – 6.3	10	290	11,600		6 – 6.3	8	232	11,600
			7 – 7.3	12	348	13,920		7 – 7.3	10	290	14,500
			9 – 32.5	14	406	16,240		9	12	348	17,400
								11 – 32.5	14	406	20,300
	19	5	5	14	266	10,640	19	5	10	190	9,500
			6 – 6.3	16	304	12,180		6 – 6.3	12	228	11,400
			7 – 7.3	18	342	13,680		7 – 7.3	14	266	13,300
			9 – 32.5	22	418	16,720		9	18	342	17,100
5	30	7 – 9 <sup>2</sup>	6	180	7,200	30	7 – 11 <sup>2</sup>	6	228	9,000	
		11 – 32.5	8	240	9,600		13.5 – 32.5	8	304	12,000	
	23	5	5 – 6.3	8	184	7,360	23	5 – 6.3	6	138	6,900
			7 – 7.3	10	230	9,200		7 – 7.3	8	184	9,200
			9 – 32.5	12	276	11,040		9	10	230	11,500
								11 – 32.5	12	276	13,800

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> For lower DR pipe, bundle weight exceeds 8,000 lbs. Use bundle having fewer joints/bundle for lower DR pipe.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA



**Table 3A (cont.) Standard Truckload Quantities – IPS-DR Pipe Joints<sup>1</sup>  
Multi-Layer Pipe Bundles**

Length IPS Pipe Size	40 ft Joint					50 ft Joint				
	Joints / Bundle	Pipe DR	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pipe DR	Bundles / Truckload	Joints / Truckload	Feet / Truckload
6	26	11 – 32.5	8	208	8,320	26	13.5 – 32.5	10	208	10,400
	20	5 – 6.3	6	120	4,800	20	13.5 – 32.5	10	200	10,000
		7 – 7.3	8	160	4,800					
		9 – 32.5	10	200	8,000					
	13	5	8	104	4,160	13	5 – 6.3	8	104	5,200
		6 – 6.3	10	130	5,200		7 – 7.3	10	130	6,500
		7 – 7.3	12	156	6,240		9	12	156	7,800
9		14	182	7,280	11		14	182	9,100	
	11 – 32.5	16	208	8,320		13.5 – 32.5	16	208	10,400	
8	14	6 – 7.3 <sup>2</sup>	6	72	3,360	14	9 <sup>2</sup>	6	84	4,200
		9 – 32.5	8	112	4,480		11 – 32.5	8	112	5,600
	9	5 – 6	8	72	2,880	9	5 – 6	6	54	2,700
		6.3 – 7.3	10	90	3,600		6.3 – 7.3	8	72	3,600
		9 – 32.5	12	108	4,320		9	10	90	4,500
							11 – 32.5	12	108	5,400
	5	5	14	70	2,800	5	5 – 6	12	60	3,000
		6 – 6.3	16	80	3,200		6.3 – 7	14	70	3,500
		7	18	90	3,600		7.3	16	80	4,000
		7.3	20	100	4,000		9	18	90	4,500
9 – 32.5		22	110	4,400	11 – 32.5		22	110	5,500	

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> For lower DR pipe, bundle weight exceeds 8,000 lbs. Use bundle having fewer joints/bundle for lower DR pipe.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA



**Table 3B Standard Truckload Quantities – IPS-DR Pipe Joints<sup>1</sup>  
Single-Layer Pipe Bundles**

Length IPS Pipe Size	40 ft. Joint					50 ft. Joint				
	Pipe DR	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pipe DR	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload
10	5		5	45	1,800	5 – 6		4	36	1,800
	6 – 7	9 (5 + 4) <sup>2</sup>	6	54	2,160	6.3 – 7.3	9 (5 + 4) <sup>2</sup>	5	45	2,250
	7.3		7	63	2,520	9		6	54	2,700
	9 – 32.5		8	72	2,880	11 – 32.5		8	72	3,600
5 – 6	4		32	1,280	5 – 6	3		24	1,200	
12	6.3 – 7.3	8 (4 + 4)	5	40	1,600	6.3 – 7.3	8 (4 + 4)	4	32	1,600
	9		7	52	2,080	9		5	40	2,000
	11 – 32.5		7	56	2,240	11		6	48	2,400
	5 – 6		3	24	1,200	13.5 – 32.5		7	56	2,800
	6.3 – 7.3		4	32	1,280	5 – 6.3		3	21	1,050
14	7 – 7.3	7 (4 + 3) <sup>2</sup>	5	35	1,400	7 – 7.3	7 (4 + 3) <sup>2</sup>	4	28	1,400
	9 – 32.5		6	42	1,680	9		5	35	1,750
	5 – 6.3		3	21	1,050	11 – 32.5		6	42	2,100
	7 – 7.3		4	28	1,400	5		3	12	750
16	9	6 (3 + 3)	6	33	1,320	6	6 (3 + 3)	3	18	900
	11 – 41		6	36	1,440	7-7.3		4	21	1,050
	5 – 6.3		3	15	600	9		5	24	1,200
	7 – 7.3		4	20	800	11		6	33	1,650
	9 – 41		5	25	1,000	13.5 – 41		6	36	1,800
18	5 – 6.3	5 (3 + 2) <sup>2</sup>	3	15	600	6 – 7.3	5 (3 + 2) <sup>2</sup>	4	17	850
	7 – 7.3		4	20	800	9		4	20	1,000
	9 – 41		5	25	1,000	11 – 41		5	25	1,250
	6 – 7.3		3	15	600	6 – 7		2	10	500
20	9 – 41	5 (3 + 2) <sup>2</sup>	4	20	800	7.3 – 9	5 (3 + 2) <sup>2</sup>	3	15	750
	6 – 7.3		3	12	480	11 – 41		4	2	1,000
	9 – 41		4	16	640	6 – 6.3		3	8	500
22	6 – 7.3	4 (2 + 2)	3	12	480	7 – 9	4 (2 + 2)	3/4	12/14	600/700
	9 – 41		4	16	640	11 – 41		4	16	800
	6.3		3	10	400	6.3 – 7		2	8	400
	7 – 9		3	12	480	7.3		3	10	500
	11 – 41		4	16	640	9		4 (2 + 2)	3	12
24	11 – 41	3 (1 + 2) <sup>2</sup>	3	9	360	11	3 (1 + 2) <sup>2</sup>	4	14	700
	7 – 41		3	9	360	13.5 – 41		4	16	800
	7 – 7.3		2	6	300	7 – 7.3		2	6	300
	9 – 41		3	9	450	9 – 41		3	9	450

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high), and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.  
<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.





## Table 3B (cont.) Standard Truckload Quantities – IPS-DR Pipe Joints<sup>1</sup> Single-Layer Pipe Bundles

Length	40 ft. Joint					50 ft. Joint				
	IPS Pipe Size	Pipe DR	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pipe DR	Joints / Layer	Layers / Truckload	Joints / Truckload
28	7.3 – 41	3 (1 + 2) <sup>2</sup>	3	9	360	7.3	3 (1 + 2) <sup>2</sup>	2	6	300
						9 – 41		3	9	450
30	9 – 41	3 (1 + 2) <sup>2</sup>	3	9	360	9	3 (1 + 2) <sup>2</sup>	2	6	300
						9.3 – 41		3	9	450
32	9 – 41	3 (1 + 2) <sup>2</sup>	2	6	240	9 – 41	3 (1 + 2) <sup>2</sup>	2	6	300
34	9 – 41	3 (1 + 2) <sup>2</sup>	2	6	240	9 – 41	3 (1 + 2) <sup>2</sup>	2	6	300
36	9 – 41	2 (1 + 1)	2	4	160	9 – 41	2 (1 + 1)	2	4	200
42	11 – 41	2 (1 + 1)	2	4	160	11 – 41	2 (1 + 1)	2	4	200
48	13.5 – 41	2 (1 + 1)	2	4	160	13.5 – 41	2 (1 + 1)	2	4	200
54	15.5 – 41	1	2 <sup>3</sup>	2	80	15.5 – 41	1	2 <sup>3</sup>	2	100

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

<sup>3</sup> Second layer (joint) offset above first layer on risers.

## Table 4A Standard Truckload Quantities – PE4710 DIPS-PC Pipe Joints<sup>1</sup> Multi-Layer Pipe Bundles

Length	40 ft Joint					50 ft Joint				
	DIPS Pipe Size	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload
4	57 <sup>2</sup>	250 – 100	6	342	13,680	57 <sup>2</sup>	200 – 100	6	342	11,400
		300	6	288	11,520		48 <sup>2</sup>	250	6	288
	48	250 – 100	8	384	15,360	38		200 – 100	8	384
		300 – 100	8	304	12,160		300	6	228	11,400
6	26	300 – 250	6	156	6,240	26 <sup>2</sup>	200	6	156	7,800
		200 – 100	8	208	8,320		150 – 100	8	208	10,400
	20	300 – 250	8	160	6,400	20	300 – 250	6	120	6,000
		200 – 100	10	200	8,000		200	8	160	8,000
	13	300	12	156	6,240	13	150 – 100	10	200	10,000
		250 – 100	14	182	7,280		300 – 250	10	130	6,500
						200 – 100	14	182	9,100	

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> For higher PC pipe, bundle weight exceeds 8,000 lbs. Use bundle having fewer joints/bundle for higher PC pipe.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA



**Table 4A (cont.) Standard Truckload Quantities – PE4710 DIPS-PC Pipe Joints<sup>1</sup>  
Multi-Layer Pipe Bundles**

Length	40 ft Joint					50 ft Joint				
	DIPS Pipe Size	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload
8	14	300	6	84	3,360	14 <sup>2</sup>	250 – 200	6	84	4,200
		250 – 100	8	112	4,480		150 – 100	8	112	5,600
	9	300 – 100	10	90	3,600	9	300 – 250	8	72	3,600
			200 – 100	10	90		4,500		300	14
	5	300	18	90	3,600	5	250	16	80	4,000
		250	20	100	4,000		200	20	100	5,000
		200 – 100	22	110	4,400		150 – 100	22	110	5,500

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> For higher PC pipe, bundle weight exceeds 8,000 lbs. Use bundle having fewer joints/bundle for higher PC pipe.

**Table 4B Standard Truckload Quantities – PE4710 DIPS-PC Pipe Joints<sup>1</sup>  
Single-Layer Pipe Bundles**

Length	40 ft. Joint					50 ft. Joint					
	DIPS Pipe Size	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload
10	300	250	9 (5 + 4) <sup>2</sup>	6	54	2,160	300	9 (5 + 4) <sup>2</sup>	5	45	2,250
				7	63	2,520	250		6	54	2,700
	200 – 100	8	72	2,880	300 – 250	5	35	1,750			
					200 – 100	8	72	3,600			
12	300 – 100	7 (4 + 3) <sup>2</sup>	6	42	1,680	300 – 250	7 (4 + 3) <sup>2</sup>	5	35	1,750	
						200 – 100		6	42	2,100	
14	300	250 – 100	6 (3 + 3)	5	30	1,200	300	6 (3 + 3)	4	24	1,200
				6	35	1,440	250		5	30	1,500
							200 – 100		6	36	1,800
16	300 – 100	5 (2 + 3) <sup>2</sup>	4	20	800	300 – 100	5 (2 + 3) <sup>2</sup>	4	20	1,000	
18	300 – 100	5 (2 + 3) <sup>2</sup>	4	20	800	300 – 250	5 (2 + 3) <sup>2</sup>	3	15	750	
						200 – 100		4	20	1,000	
20	300 – 100	4 (2 + 2)	4	16	640	300 – 250	4 (2 + 2)	3	12	600	
						200 – 100		4	16	800	
24	300 – 100	3 (2 + 1) <sup>2</sup>	3	9	360	300 – 100	3 (2 + 1) <sup>2</sup>	3	9	450	

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high), and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA



**Table 4B (cont.) Standard Truckload Quantities – PE4710 DIPS-PC Pipe Joints<sup>1</sup>**  
**Single-Layer Pipe Bundles**

Length	40 ft. Joint					50 ft. Joint				
DIPS Pipe Size	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload
30	200 – 100	3 (2 + 1) <sup>2</sup>	2	6	240	200 – 100	3 (2 + 1) <sup>2</sup>	2	6	300
36	150 – 100	2	2	4	160	150 – 100	2	2	4	200

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high), and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

**Table 5A Standard Truckload Quantities – FM Approved Pipe Joints<sup>1</sup>**  
**Multi-Layer Pipe Bundles**

Length	40 ft Joint					50 ft Joint				
IPS Pipe Size	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload
4	57	200	8	456	18,240	57	200	8	456	22,800
		250	8	456	18,240		250	6	342	17,100
		335	6	342	13,680		335	NR <sup>2</sup>	NR <sup>2</sup>	NR <sup>2</sup>
	29	200	16	464	18,560	29	200	14	406	20,300
		250	14	406	16,240		250	12	348	17,400
		335	12	348	13,920		335	10	290	14,500
19	200	22	418	16,720	19	200	22	418	20,900	
	250	22	418	16,720		250	18	342	17,100	
	335	18	342	13,680		335	14	266	13,300	
6	20	200	10	200	8,000	20	200	10	200	10,000
		250	10	200	8,000		250	8	160	8,000
		335	8	160	6,400		335	8	160	8,000
	13	200	16	208	8,320	13	200	14	182	9,100
		250	14	182	7,280		250	12	156	7,800
		335	12	156	6,240		335	10	130	6,500

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Not recommended. Bundle weight exceeds 8,000 lbs. Use bundle having fewer joints/bundle.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.





# WL108 SHIPPING DATA



**Table 5A (cont.) Standard Truckload Quantities – FM Approved Pipe Joints<sup>1</sup>  
Multi-Layer Pipe Bundles**

Length IPS Pipe Size	40 ft Joint					50 ft Joint				
	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload	Joints / Bundle	Pressure Class	Bundles / Truckload	Joints / Truckload	Feet / Truckload
8	14	200	8	112	4,480	14	200	8	112	5,600
		250	8	112	4,480		250	6	84	4,200
		335	6	84	3,360		335	4	56	2,800
	9	200	12	108	4,320	9	200	12	108	5,400
		250	12	108	4,320		250	10	90	4,500
		335	10	90	3,600		335	8	72	3,600
	5	200	22	110	4,400	5	200	22	110	5,500
		250	22	110	4,400		250	18	90	4,500
		335	18	90	3,600		335	14	70	3,500

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high) and full load width layers. Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

**Table 5B Standard Truckload Quantities – FM Approved Pipe Joints<sup>1</sup>  
Single-Layer Pipe Bundles**

Length IPS Pipe Size	40 ft. Joint					50 ft. Joint				
	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload
10	200	9 (4 + 5) <sup>2</sup>	8	72	2,880	200	9 (4 + 5) <sup>2</sup>	8	72	3,600
	250	9 (4 + 5) <sup>2</sup>	8	72	2,880	250	9 (4 + 5) <sup>2</sup>	7	59	2,950
	335	9 (4 + 5) <sup>2</sup>	6	54	2,160	335	9 (4 + 5) <sup>2</sup>	5	45	2,250
12	200	8 (4 + 4)	7	56	2,240	200	8 (4 + 4)	6	48	2,400
	250	8 (4 + 4)	6	48	1,920	250	8 (4 + 4)	5	40	2,000
	335	8 (4 + 4)	5	40	1,600	335	8 (4 + 4)	4	32	1,600
14	200	7 (4 + 3) <sup>2</sup>	6	42	1,680	200	7 (4 + 3) <sup>2</sup>	6	42	2,100
	250	7 (4 + 3) <sup>2</sup>	6	42	1,680	250	7 (4 + 3) <sup>2</sup>	5	35	1,750
	335	7 (4 + 3) <sup>2</sup>	5	35	1,400	335	7 (4 + 3) <sup>2</sup>	4	28	1,400
16	200	6 (3 + 3)	5	30	1,200	200	6 (3 + 3)	6	33	1,650
	250	6 (3 + 3)	5	30	1,200	250	6 (3 + 3)	4	24	1,200
	335	6 (3 + 3)	4	24	960	335	6 (3 + 3)	4	22	1,100
18	200	5 (3 + 2) <sup>2</sup>	4	20	800	200	5 (3 + 2) <sup>2</sup>	4	20	1,000
	250	5 (3 + 2) <sup>2</sup>	4	20	800	250	5 (3 + 2) <sup>2</sup>	4	20	1,000
	335	5 (3 + 2) <sup>2</sup>	4	20	800	335	5 (3 + 2) <sup>2</sup>	4	17	850
20	200	5 (3 + 2) <sup>2</sup>	4	20	800	200	5 (3 + 2) <sup>2</sup>	4	20	1,000
	250	5 (3 + 2) <sup>2</sup>	4	20	800	250	5 (3 + 2) <sup>2</sup>	3	15	750
	335	5 (3 + 2) <sup>2</sup>	3	15	600	335	5 (3 + 2) <sup>2</sup>	2	10	500

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.



# WL108 SHIPPING DATA

**Table 5B (cont.) Standard Truckload Quantities – FM Approved Pipe Joints<sup>1</sup>  
Single-Layer Pipe Bundles**

Length	40 ft. Joint					50 ft. Joint					
	IPS Pipe Size	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload	Pressure Class	Joints / Layer	Layers / Truckload	Joints / Truckload	Footage / Truckload
22	200		4 (2 + 2)	4	16	640	200	4 (2 + 2)	4	16	800
	250		4 (2 + 2)	4	16	640	250	4 (2 + 2)	3	12	600
	335		4 (2 + 2)	3	12	480	335	4 (2 + 2)	3	12	600
24	200		4 (2 + 2)	3	12	480	200	4 (2 + 2)	3	12	600
	250		4 (2 + 2)	3	12	480	250	4 (2 + 2)	3	12	600
	335		4 (2 + 2)	3	12	480	335	4 (2 + 2)	2	8	400
26	200		3 (2 + 1) <sup>2</sup>	3	9	320	200	3 (2 + 1) <sup>2</sup>	3	9	450
	250			3	9	320	250		3	9	450
28	200		3 (2 + 1) <sup>2</sup>	3	9	320	200	3 (2 + 1) <sup>2</sup>	3	9	450
	250			3	9	320	250		3	9	450
30	200		3 (2 + 1) <sup>2</sup>	3	9	320	200	3 (2 + 1) <sup>2</sup>	3	9	450
	250			3	9	320	250		3	9	450
32	200		3 (2 + 1) <sup>2</sup>	3	9	300	200	3 (2 + 1) <sup>2</sup>	3	8	400
	250			3	9	300	250		3	8	400
34	200		3 (2 + 1) <sup>2</sup>	2	6	240	200	3 (2 + 1) <sup>2</sup>	2	6	300
	250			2	6	240	250		2	6	300
36	200		2 (1 + 1)	2	4	160	200	2 (1 + 1)	2	4	200
	250			2	4	160	250		2	4	200

<sup>1</sup> Table quantities based on WL Plastics standard packaging for multi-layer and single layer bundles and strip-loads. Special packaging and joint lengths may be available. Truckload capacity based on DOT maximum load weight of 47,000 lb (21,364 kg) and maximum load dimensions 102" high x 102" wide (2.6 m wide x 2.6 m high). Special load configurations may be available and actual shipping equipment size may affect truckload capacity. Contact WL Plastics Customer Service for information.

<sup>2</sup> Layers are interlaced, e.g., 1<sup>st</sup> layer – odd + even; 2<sup>nd</sup> layer – even + odd; 3<sup>rd</sup> layer odd + even, etc.

This publication is intended for use as a piping system guide. The information in this publication does not constitute a guarantee or warranty for piping installations and cannot be guaranteed because the conditions of use are beyond our control. Changes to this publication may occur from time to time without notice. Contact WL Plastics Corporation to determine if you have the most current edition.

